

CoBox™ Interface Specifications:

Protocols	TCP/IP
Ports	
Network	RJ45 (10Base-T) and AUI Ethernet
Serial	DB25 serial port, DTE configuration
Network Bandwidth Usage	37,000 bps max. (0.4%) 10Base-T (master/slave polling architecture; not broadcasting)
Serial Line Formats	Characters: 7 or 8 data bits Stop bits: 1 or 2 Parity: odd, even, none
Modem Controls	RTS, CTS, DSR, DCD, DTR
Flow Control	Xon/Xoff RTS/CTS None
Management	via serial port

• System Software

Flash ROM standard; new software can be downloaded via the serial port

• Diagnostic LEDs

Network: Transmit Data, Receive Data, Good Link, Collisions (Ethernet Only)

Serial Ports: Channel status, fault indicator

• Compatibility

Ethernet: Version 2.0/IEEE 802.3

• Power Requirements

External 230VAC adapter with Euro connector included.

Input power requirements: 16 VAC @ .9A

Power consumption: 9 Watts

• Environmental

Operating Temperatures: 5 to 50C (41 to 122F)

Storage Temperatures: -40 to 66C (-40 to 151F)

• Physical Dimensions

Height: 4.0 cm (1.57 in)

Width: 15.5 cm (6.10 in)

Depth: 18.0 cm (7.00 in)

Weight: .5kg

Copyright © 2000, Checkpoint Systems ACPG, [GMR Communications](#)
& [Media Fusion Technologies, Inc.](#)

All Rights Reserved.

Copy and/or distribution in any form is strictly prohibited.